



CLEARRAY™ WATER CARE SYSTEM

- Start Up:**
1. Fill spa with clean water through filter compartment.
 2. Turn on power to spa at the home's circuit breaker.
 3. Insert Jacuzzi ProClear® Cartridge into filter compartment.
 4. Adjust pH 7.4 - 7.6; Total alkalinity 100 - 120; and Calcium Hardness 150 - 250.
 5. Add 1 oz. Granular Chlorine (Dichlor) per 250 gallons, add this with jet pump running for 30 minutes and cover open.
 6. Wait 48 hours , add stain and scale control per labeled instructions.
- Daily:**
1. Test Chlorine. Maintain a minimum 1ppm Chlorine level.
 2. If Chlorine level is less than 1ppm add 1/4 oz. of Granular Chlorine (Dichlor) per 250 gallons.
- After Each Use:**
1. Add 1 oz Non Chlorine shock with jet pump running.
- Weekly:**
1. Test pH, and Total Alkalinity levels of the spa, preferably two to three times weekly.
 2. Add stain and scale inhibitor per labeled instructions.
 3. If pH is does not fall within the range of 7.4 - 7.6, adjust as needed with pH Up or pH Down.
 4. Add 1/4 oz Granular Chlorine(Dichlor) per 250 Gallons
- Monthly:**
1. Rinse filters with water.
- Every 3 to 4 Months:**
1. Chemically clean your filter(s) using a filter degreaser.
 2. Drain, clean and refill your spa.
 3. Clean cover with 303 protectant.
 4. Replace ProClear® Mineral Cartridge
- Annually:**
1. Replace CLEARRAY™ Bulb and clean quartz tube.
 2. Inspect filters and replace if necessary.
- Measurements:**
- 1/4 oz. = 1 teaspoon 3/4 oz. = 1 tablespoon
- Other Tips:** If water becomes hazy, test and adjust pH and Total Alkalinity, then add 1 oz Granular Chlorine (Dichlor) per 250 gallons. Leave cover open with jet pump running for 30 minutes.
- Filtration:** The continuous filtration pump on J400's and J300's are preprogrammed to operate 8 hours per day. If you encounter water clarity issues increase filter pump to 24 hours per day. Reference owner's manual for instructions on how to make this change.